



Water, Electric Energy and Flood

Oleg Khalidullin*

Independent Researcher, Almaty, Republic of Kazakhstan

*Corresponding author: Oleg Khalidullin, Independent Researcher, Almaty, Republic of Kazakhstan

Received: 📅 February 26, 2019

Published: 📅 March 06, 2019

Short Communication

Ways of water conservation in rivers are based on the creation of bulky dams with flooding of large areas and the creation of hydroelectric power plants (HPP). Man-made reservoirs are built on all residential continents, occupying more and more large areas with the destruction of biota. For example, 280 hydroelectric power plants are under construction in South America. In China - <http://www.rukivnogi.com/articles/top-10-samyh-bolshih-ges-v-mire>: "In front of the hydroelectric dam, a large reservoir was formed, containing 22 cu. km of water and having a water surface area of 1045 square meters. km In Brazil, 24 electric generators were recently installed on the dam. The volume of water in the reservoir almost reaches 46 cubic kilometers, and the surface area of the water is 2430 square meters. km In Russia, a hydroelectric dam holds the mass of a large Krasnoyarsk reservoir, having a water surface area of approximately 2000 square meters. km. " The main trouble of all reservoirs is the risk of breaking through and destroying everything below the dams. No less trouble is that the biota disappears under the reservoir mirror, and with it, the mechanism of water conversion in the animal and plant worlds, accumulated over millions of years. The area of plant leaves alone is 3 to 4 times the area of the entire land. The size of it, not less than the area of the oceans - <https://vuzlit.ru/984043/transpiratsiya> # 597. This is in untouched land, now by 2015, this land remains 30%. Everything else is plowed up, dumped by dumps, rolled up with asphalt. The natural water path on land is movement along the biota food and plant paths. Humanity at an accelerating pace destroys recent natural ranges.

According to the Latest Theory on Climate Change

<https://juniperpublishers.com/jojwb/pdf/JOJWB.MS.ID.555551.pdf> flooding of territories is the destruction of organic and increasing artificial evaporation, which leads the planet to natural disasters and global catastrophe. If you look at the river, we often hear and see water overflowing and devastating floods.

The main cause of such flooding is shallowing of rivers. By nature, the water continuously washes away soil particles from the banks and places them on the bottom. To this was added the human factor - garbage, waste products, various items in the form of scrap - add a significant increase in raising the bottom. Statistics were not found, but, logically, it is the coastal territories of settlements that are more destroyed. Rubbish discharged into rivers and settlements forms "thrombi" - underwater dams along the stream of water in the beds along the cities and downstream. This is where the most water comes out of the coast. Rivers, with increasing bottom intensively change their channel, expand the floodplains and overflow. To avoid this, it is necessary to maintain the depth, regularly remove sediment. But this is not the main thing, the main thing is that if we want to save the planet for our descendants, we must immediately begin to return to the water its natural functions.

One of the main elements of reducing artificial evaporation is the cessation of the construction of new hydropower plants with the flooding of areas and the release of all previously built reservoirs. This is the conclusion reached by Chinese experts of the Academy of Sciences of China: http://www.trud.ru/article/27-11-2018/1369666_kitajskie_akademiki_prizvali_snesti_tysjachi_ges_na_reke_jantszy.html. In the USA, for example, over half a century, more than 250 unprofitable hydroelectric power plants were decommissioned - <https://glavred.info/politics/404585-ges-dneprovskogo-kaskada-ili-mina-zamedlennogo-deystviya.html>

There is a brilliant invention of V.I. Bodyakina https://docviewer.yandex.ru/view/0/?*=L%2FAL7lzYSYbEAFtue6KjdIj5t97InVybcI6InlhLWJyb3dzZXI6Ly80RFQxdVhFUFJySIJYbFVGb2V3cnVKdTNxLXQwc0trVEJlTDI4MTZvV2E3TGdaWUzZfZzdXWHk1U0ZlQ2YxN2tsTHo1a3JaU19CNWZSYjZveFBWZDI3WXcZdzlUTFo5UnNjMU1jQ1lTTVlKSjcyH5RkMtaHc2Wjd6U2s5QmtJbS0tUmzczTk4UGo30FJB0GVVclhrMXc9PT9zaWduPWIMRzgyM0oyZGZLT

VotbDZKS1JuRmJvcUdzcMtRTFZVExrRI9zNmFlbDA9IiwidGI0bGUiOijWb2RveF9WLMrvYyIsInVpZCI6IjAiLCJ5dSI6IjEwNjM4MTcwODE1NDk3NTMzMjUiLCJub2lmc m FtZSI6ZmFsc2UsInRzljoxNTUwMjg3NjE2Nz M4fQ%3D%3D&page=2, which maintains the existing power generation of hydroelectric generators without dams. The pressure creates water moving in the pipes from the beginning of the reservoir with the rise to the former top of the dam.

It is necessary to fundamentally review the possibility of accumulation of water in rivers. The accumulation of water for irrigation and selection for cities can be created by small dams. Considering the levels of rivers and their floodplains, we find a fairly large difference in the height of the water level in the river and the height of the banks of the floodplains. In essence, the narrow, winding river at the bottom of the floodplain is not normal. The entire area, periodically washed away by the spring waters for centuries, is a drying stone-sand bank, often overgrown with various plants, which at certain points of the meandering of the river are washed away and carried away along the stream. There are absolutely bare areas of floodplain without plants - only sand and stones. This state suggests that the floodplains can be used to accumulate water in the spring and consume it in the summer. To do this, it is enough to build a dam in the given places with a height not exceeding the height of the floodplain coast. And fill it to the brim. Many such dams form a cascade of lakes with running water. Like the famous cascades on the Volga and other rivers with giant dams. Naturally, in the body of such dams, culverts are constructed for taking water, spawning fish, moving ships, and regulating levels in adjacent pools. It is also possible to install small hydropower plants operating at a small height difference. There are no problems with dam structures 5–20 meters high. The usual earth-moving and road equipment is used.

There are places where there is no floodplain, and in these places the water overflows, often with floods. And floods in them come from the same reasons - silting and raising the bottom. On such sections of the river there are stretches and rifts. So, these natural stretches

should be deepened up to 10-30 meters, and the rapids - shoals rise to the level of the shores, also with the installation of culverts. These works can be performed with existing dredging equipment. It is cumbersome, energy-intensive and requires sufficiently large labor costs. There are a number of inventions that allow you to carry out any dredging work and solve the tasks with minimal cost. Use mainly the flow of the river itself. The essence of inventions is described in the articles: <https://www.omicsonline.org/open-access/prevention-of-floods-2332-2608-1000246-94678.html>, <https://www.actascientific.com/ASAG/pdf/ASAG-02-0128.pdf>.


All these inventions are made in the form of proprietary technical solutions and require research and development. Thus, it is possible to save water of the same volumes as in reservoirs with bulky dams, but without the risks of man-made disasters. In foothill and mountain rivers, a chain of lakes with adjustable pools can become an obstacle to mudflows, and the water surface, covering the narrow, blurred, disfigured multimeter in height, gorges among fir trees will adorn the mountain landscape. The river becomes a distributed water reservoir, which changes the regime of small and intermittent rivers. They can become navigable, they can generate electricity, and according to the ideas of V.I. Bodyakin, using pipes, it is possible to save the generators of existing hydroelectric stations without dams. Where there is no hydroelectric station, it is possible to create a micro hydroelectric station, distributed along the entire length of the river. In addition, new, unprecedented properties are added - all the rivers and even small ones become fish-breeding, with bridges in given places, the possibilities of organizing beaches, recreation areas. Small rivers become navigable and will not dry out during dry periods. The management capabilities of culvert constructions will allow to exclude the movement of ice in the springtime, and, consequently, floods due to congestion and blockages. In the mountain rivers, a new strategy of protection is being created. An important, if not paramount, factor in reducing political tensions in the world, if such a concept is adopted, will be that all transboundary rivers will no longer be problematic in terms of water distribution.



This work is licensed under Creative Commons Attribution 4.0 License

To Submit Your Article Click Here: [Submit Article](#)

DOI: [10.32474/OAJESS.2019.02.000136](https://doi.org/10.32474/OAJESS.2019.02.000136)



Open Access Journal of Environmental and Soil Sciences

Assets of Publishing with us

- Global archiving of articles
- Immediate, unrestricted online access
- Rigorous Peer Review Process
- Authors Retain Copyrights
- Unique DOI for all articles